

DIESEL

0.007



NO.	PROPERTIES	UNIT	RESULT	TEST METHOD
1.	Density@15°C	Kg/m ³	820 - 860	ASTM D1298
2.	Distillation	-	-	-
3.	Recovered@150°C	Vol%	Report	ASTM D86
4.	Recovered@300°C	Vol%	Report	ASTM D86
5.	Recovered@357°C	Vol%	90 min	ASTM D86
6.	FBP	°C	385 max	ASTM D86
7.	Corrosion 3hr@100°C	-	1a	ASTM D130
8.	Kinematic viscosity@37.8°C	CST	2.0 - 5.5 max	ASTM D445
9.	Cloud point	°C	2 max	ASTM D2500
10.	Sulphur total	Wt%	0.7 max	ASTM D1552
11.	Carbon residue	Wt%	0.1 max	ASTM D189
12.	Color	-	3 max	ASTM D1500
13.	Flash point	°C	54 min	ASTM D93
14.	Pour point	°C	3 max	ASTM D97
15.	Ash	WT%	0.01 max	ASTM D482
16.	Water & sediment	Vol%	0.05 max	ASTM D2709
17.	Cetane index	-	50 min	ASTM D976

The analysis will be customizable & produce able as per buyer's request