

# GASOLINE

## A95



NO.	PROPERTIES	UNIT	RESULT	TEST METHOD
1.	RON	-	Min 95	ASTM D 2699
2.	MON	-	Min 84	ASTM D 2700
3.	Density@15°C	Kg/m <sup>3</sup>	740	ASTM D 4052
4.	DVPE	Kpa	58	ASTM D 232
5.	IBP	°C	40	ASTM D 86
6.	10%	°C	57	ASTM D 86
7.	50%	°C	113	ASTM D 86
8.	90%	°C	143	ASTM D 86
9.	FBP	°C	193	ASTM D 86
10.	Residue	%Vol	1	ASTM D 86
11.	Losses	%Vol	2	ASTM D 86
12.	E70	%Vol	32	EN ISO 3405
13.	E100	%Vol	45	EN ISO 3405
14.	E150	%Vol	91	EN ISO 3405
15.	Oxygen	%mass	1.95	EN 1601
16.	Sulphur	Mg/kg	150	ASTM D 4294
17.	Saturate	%Vol	58	ASTM D 1319
18.	Aromatic	%Vol	35	ASTM D 1319
19.	Olefin	%Vol	2	ASTM D 1319
20.	Benzene	%Vol	0.9	EN 238
21.	Ethanol	%Vol	0.0	EN 1601
22.	Methanol	%Vol	0.0	EN 1601
23.	Oxide stability	Minutes	>960	ISO 7536
24.	Copper strip	Merit	1a	ISO 2160
25.	Existent gum	Mg/100ml	<5	ISO 6246
26.	Water content	ppm	120	EN ISO 12937

**The analysis will be customizable & produce able as per buyer's request**



**TAJIK OIL REFINING**